




AMERICAN NTN BEARING LTD

85 mm x 120 mm x 18 mm SKF S71917 ACB/HCP4A angular contact ball bearings

Bearing No. S71917 ACB/HCP4A



S71917 ACB/HCP4A Bearing 2D drawings and 3D CAD models

Size	120x85x18 mm
Bore Diameter	120 mm
Outer Diameter	85 mm
Width	18 mm
d	85 mm
D	120 mm
B	18 mm
d ₁	98.2 mm
d ₂	96.7 mm
D ₂	110.2 mm
r _{1,2} - min.	1.1 mm
r _{3,4} - min.	0.6 mm
a	36.3 mm
d _a - min.	91 mm
d _a - max.	97.5 mm
d _b - min.	91 mm
d _b - max.	96 mm
D _a - max.	114 mm
D _b - max.	116.8 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
Basic dynamic load rating - C	15.3 kN
Basic static load rating - C ₀	15.3 kN
Fatigue load limit - P _u	0.64 kN



AMERICAN NTN BEARING LTD

Limiting speed for grease lubrication	16000 r/min
Ball - D_w	6.747 mm
Ball - z	37
Calculation factor - e	0.68
Calculation factor - Y_2	0.87
Calculation factor - Y_0	0.38
Calculation factor - X_2	0.41
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Preload class A - G_A	93 N
Preload class B - G_B	185 N
Preload class C - G_C	560 N
Calculation factor - f	1.11
Calculation factor - f_1	0.99
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2C}	1.08
Calculation factor - f_{HC}	1.01
Preload class A	151 N/micron
Preload class B	195 N/micron
Preload class C	296 N/micron
d_1	98.2 mm
d_2	96.7 mm
D_2	110.2 mm
$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
d_a min.	91 mm



AMERICAN NTN BEARING LTD

d_a max.	97.5 mm
d_b min.	91 mm
d_b max.	96 mm
D_a max.	114 mm
D_b max.	116.8 mm
r_a max.	1 mm
r_b max.	0.6 mm
Basic dynamic load rating C	20.3 kN
Basic static load rating C_0	24.5 kN
Fatigue load limit P_u	0.64 kN
Attainable speed for grease lubrication	16000 r/min
Ball diameter D_w	6.747 mm
Number of balls z	37
Preload class A G_A	93 N
Static axial stiffness, preload class A	151 N/ μ m
Preload class B G_B	185 N
Static axial stiffness, preload class B	195 N/ μ m
Preload class C G_C	560 N
Static axial stiffness, preload class C	296 N/ μ m
Calculation factor f	1.11
Calculation factor f_1	0.99
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.08
Calculation factor f_{HC}	1.01
Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38



AMERICAN NTN BEARING LTD

Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	0.56 kg